

# M30D

Powersoft

2-Channel Power Amplifier for Portable and Permanently Installed Applications



- ✓ Touring
- ✓ Installation

2CH



- ▶ Small to medium-scale systems, portable and installed
- ▶ Subwoofers
- ▶ Fullrange loudspeakers
- ▶ Hotels, restaurant and bars
- ▶ Amusement parks, themed entertainment
- ▶ Houses of worship, auditoriums
- ▶ Educational facilities
- ▶ Live and dance clubs
- ▶ Mobile DJ's

Equally versatile in both portable and installed system configurations and with delivering up to 3,000 W out of one single rack unit weighing just over 7 kg / 16 lb, the **M30D** is a flexible, cost-effective solution for small to medium sound systems.

Benefitting from core technologies of Powersoft's flagship K Series, the **M30D** sets a class standard in efficiency, leading to low power consumption, and consequently to substantial money savings on electricity, all in an eco-friendly way.

Minimum heat dissipation makes the **M30D** suitable for hot or otherwise challenging environments.

Added the legendary sound quality thanks to Powersoft's unique, patented Class D output stage design, the **M30D** represents a fantastic value, practically as well as commercially.

The **M30D** comes with 4 years warranty and, like all Powersoft products, is entirely designed and made in Italy.

2-channel mode				mono-bridged mode
4 Ω / Ch	8 Ω / Ch	70 V <sup>1)</sup>	100 V <sup>2)</sup>	8 Ω / Ch pair
1,500 W	900 W	1,200 W	1,500 W	3,000 W


EIAJ Test Standard, 1 kHz, 1% THD

- ✓ **Legendary Powersoft efficiency:**
  - ▶ Compact and space saving: 1 RU at 358 mm / 14.1" depth
  - ▶ Green Audio Power®: minimal "carbon footprint" and operational cost of electricity
  - ▶ Plenty of power, little weight: up to 3,000 W in 7.3 kg / 16 lb
- ✓ **Unique Powersoft technology for efficient, reliable performance:**
  - ▶ Switch mode power supply, internally switchable 230/115 V nominal
  - ▶ Fixed frequency switch mode amplifier output stages
  - ▶ Patented amplifier output filters with ripple cancellation network
- ✓ **Driving distributed line systems:**
  - ▶ Able to drive 100 V distributed lines directly without the need for transformers<sup>1)</sup>
- ✓ Optimized for 4 Ω loads, thus ideally matching real-world scenarios in targeted applications
- ✓ Fully protected circuit design:
  - ▶ AC protection: shuts down power supply when AC mains voltage is outside operating range
  - ▶ Clip limiter: prevents severely clipped waveforms from reaching loudspeakers, while still maintaining full peak power output
  - ▶ DC protection: protects against infrasonic signal at the outputs
  - ▶ VHF protections: protects the loudspeakers against destructive non-audible, non-musical high frequency signals
  - ▶ Short circuit protection: protects the amplifier from short circuit or similar events on the outputs; with automatic protection reset
  - ▶ Thermal protection: mutes outputs once output devices reach 75 °C / 167 °F; automatic unmute once temperature is down to 65 °C / 149 °F
- ✓ Temperature controlled continuous variable speed fan, front to rear airflow
- ✓ Recessed stepped level attenuators
- ✓ Full four years warranty
- ✓ Also available as M30D HDSP+ETH with integrated DSP and Ethernet comm port

1) External high-pass filter and voltage limiter required.

2) External high-pass filter required.

Powersoft



### Specifications

<b>General</b>					
Number of channels	2				
Output power	2-channel mode				mono-bridged mode
EIAJ Test Standard, 1 kHz, 1% THD	4 Ω / Ch	8 Ω / Ch	70 V <sup>1)</sup>	100 V <sup>2)</sup>	8 Ω / Ch pair
	1,500 W	900 W	1,200 W	1,500 W	3,000 W
Max output voltage / current	135 V <sub>peak</sub> / 65 A <sub>peak</sub>				
<b>AC Mains Power</b>					
Power supply	Universal, regulated switch mode				
Operating voltage / Inrush current	115 V / 230 V (factory selection) ± 15%, 50 Hz - 60 Hz / < 28 A <sub>RMS</sub>				
Consumption / current draw	@ 230 V		@ 115 V		
Idle	37 W	0.3 A	37 W		0.6 A
1/8 of max output power @ 4 Ω	530 W	3.54 A	530 W		7 A
1/4 of max output power @ 4 Ω	1,024 W	6.52 A	1,024 W		13.04 A
<b>Thermal</b>					
Environmental operating temperature	0° - 45° C / 32° - 113° F				
Thermal dissipation	Fan, continuously variable speed, temperature controlled, front to rear airflow				
Idle	126 BTU/h				32 kcal/h
1/8 of max output power @ 4 Ω					133 kcal/h
1/4 of max output power @ 4 Ω					236 kcal/h
<b>Audio</b>					
Gain	32 dB, 30 dB, 28 dB, 26 dB, 24 dB, 22 dB, 20 dB, 18 dB, 14 dB, 4 dB, -∞, user selectable				
Frequency response	10 Hz - 30 kHz (1 W @ 8 Ω, ± 3 dB)				
S/N ratio (amplifier section)	>11 dBA (20 Hz - 20 kHz, A weighted)				
Crosstalk separation	>70 dB @ 1 kHz				
Input sensitivity @ 8 Ω	2.13 V / 8.8 dBu				
Max input level	6 V / 17.7 dBu				
Input impedance	10 kΩ				
THD+N / SMPTE IMD	≤ 0.07% @ 1/2 of full power				
DIM100 IMD	typ. <0.005% (<0.02% @ >0.1 W)				
Slew rate	40 V/μs @ 8 Ω, input filter bypassed				
Damping factor @ 8 Ω	>5000 @ 100 Hz				
<b>DSP (optional)</b>					
A/D converter	CS5381, 2 channels, 24 bit / 48 kHz, 120 dB SNR				
D/A converter	CS4398, 2 channels, 24 bit / 48 kHz, 120 dB SNR				
Frequency response @ -3 dB	7 Hz - 22 kHz				
THD	< 0.01% (20 Hz - 20 kHz)				
Presets	Bank of 4 presets, management and upload via Armonia Pro Audio Suite™				
Delay for time alignment	10 ms per output				
Crossover filters	Butterworth, Linkwitz-Riley, Bessel, 6 dB/oct to 48 dB/oct				
Output equalizer	up to 12 biquad fully parametric per channel: peaking, hi/lo shelving, hi/lo pass, band pass, band stop, all pass.				
Input equalizer	up to 5 biquad filters (PEQ, shelving, band pass, band stop, all pass)				
Limiters	Peak limiter, RMS limiter, frequency dependent RMS limiter				
Damping control	< 120 Hz, range ± 2 Ω				
System Delay	up to 170 ms for 2 IN/2 OUT or 340 ms for 1 IN/2 OUT				
<b>Front Panel</b>					
Indicators	4 LEDs per channel: 3 x green, 1 x red 2 status LEDs: 1 x green, 1 x yellow				
Controls	1 stepped level attenuator pot per channel; mains switch				
Maintenance	Dust filter foam behind front panel				
<b>Rear Panel</b>					
Audio signal input connectors	2 x balanced Neutrik® XLR female				
Loudspeaker output connectors	2 x Neutrik® Speakon NL4MD, 2 x Neutrik® XLR male hard-wired to the corresponding input				
Network data port Ethernet	1 x RJ45 with activity LED with 2 rotary address switches				
DSP preset selection	1 x Pushbutton (stepping through bank of 4 presets) 1 x 4 LED preset indicators				
Aux voltage	1 x 2-pin Phoenix type MC 1.5/2-ST-3.81				
AC mains	IEC C13 16 A connector; AC mains cord with 3-pin plug 15 A for US, IEC Schuko 16 A for every other nation				
Controls	1 x link switch, linking analog inputs 1 & 2				
<b>Construction</b>					
Dimensions	W 483 mm / 19", H 44.5 mm / 1.75", D 358 mm / 14.1"				
Chassis	1 mm (0.04") steel chassis and steel removable dust cover, 3 mm (0.12") steel front panel, screw hole protection, steel side reinforcement & rear support				
Weight	7.3 kg / 16 lb				

1) External high-pass filter and output voltage limiter required.  
2) External high-pass filter required.

Data is subject to change without notice.  
© 2012 Powersoft • All rights reserved.